


# Damping tools



● ● ● ● Vibration-free cutting


# Turning damping tool holder



Type	Overall length L	Holder Diameter D1	Head Diameter D2	Screw	Wrench	CNT	Inventory
KD16-7D-156	6.14"	0.63"	16	HSS3-8	L2-2.5	PN1/8-C08	★
KD20-7D-200	7.87"	0.79"	20	HSS3.5-8	L2-3	PN1/8-C08	★
KD25-7D-252	9.92"	0.98"	25	HSS4-10	L2-3	PN1/4-C08	★
KD25-10D-330	13.00"	0.98"	25	HSS4-10	L2-3	PN1/4-C08	★
KD32-7D-320	12.6"	1.26"	32	HSS5-12	L2-4	PN1/4-C08	★
KD32-10D-416	16.38"	1.26"	32	HSS5-12	L2-4	PN1/4-C08	★
KD40-7D-400	15.75"	1.57"	40	HSS6-14	L2-5	PN1/4-C08	★
KD40-10D-520	20.47"	1.57"	40	HSS6-14	L2-5	PN1/2-C10	★
KD50-7D-510	20.08"	1.97"	40	HSS6-14	L2-5	PN1/2-C10	★
KD50-10D-650	25.6"	1.97"	40	HSS6-14	L2-5	PN1/2-C10	★
KD60-7D-620	24.41"	2.36"	40	HSS6-14	L2-5	PN1/2-C10	★
KD60-10D-808	31.81"	2.36"	40	HSS6-14	L2-5	PN1/2-C10	★
KD80-8D-860	33.86"	3.15"	40	HSS6-14	L2-5	PN1/2-C10	★
KD80-10D-1200	47.24"	3.15"	40	HSS6-14	L2-5	PN1/2-C10	★
KD100-8D-1000	39.37"	3.94"	40	HSS6-14	L2-5	PN1/2-C10	★
KD100-10D-1200	47.24"	3.94"	40	HSS6-14	L2-5	PN1/2-C10	★
KD120-10D-1900	74.8"	4.72"	40	HSS6-14	L2-5	PN3/4-C10	☆
KD130-10D-2000	78.74"	5.12"	40	HSS6-15	L2-5	PN3/4-C10	☆
KD140-10D-2200	86.61"	5.52"	40	HSS6-16	L2-5	PN3/4-C10	☆
KD150-10D-2400	94.49"	5.91"	40	HSS6-15	L2-5	PN3/4-C10	☆
KD160-10D-2600	102.36"	6.3"	40	HSS6-16	L2-5	PN3/4-C10	☆


# Turning damping tool head

**DC\*\***



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D16-SDXCR/L07	16	0.87"	0.51"	0.79"	0.6"	T8	CS2.5X6	DC**0702**
D20-SDXCR/L07	20	1.02"	0.59"	0.79"	0.6"	T8	CS2.5X6	DC**0702**
D25-SDXCR/L07	25	1.26"	0.71"	0.79"	0.6"	T8	CS2.5X8	DC**0702**
D32-SDXCR/L11	32	1.54"	0.87"	1.1"	0.79"	T15	CS4X10	DC**11T3**
D40-SDXCR/L11	40	1.89"	1.06"	1.1"	0.79"	T15	CS4X12	DC**11T3**


**DC\*\***



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D16-SDUCR/L07	16	0.79"	0.43"	-	0.79"	T8	CS2.5X6	DC**0702**
D20-SDUCR/L11	20	0.94"	0.51"	-	0.79"	T15	CS4X8	DC**11T3**
D25-SDUCR/L11	25	1.18"	0.67"	-	0.79"	T15	CS4X10	DC**11T3**
D32-SDUCR/L11	32	1.54"	0.87"	-	1.26"	T15	CS4X10	DC**11T3**
D40-SDUCR/L11	40	1.89"	1.06"	-	1.26"	T15	CS4X12	DC**11T3**


# Turning damping tool head

## DC\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D16-SDZCR/L07	16	0.87"	0.51"	1.06"	0.59"	T8	CS2.5X6	DC**0702**
D20-SDZCR/L07	20	1.02"	0.59"	1.06"	0.59"	T8	CS2.5X6	DC**0702**
D25-SDZCR/L07	25	1.26"	0.71"	1.06"	0.59"	T8	CS2.5X8	DC**0702**
D32-SDZCR/L11	32	1.54"	0.87"	1.5"	0.79"	T15	CS4X10	DC**11T3**
D40-SDZCR/L11	40	1.89"	1.06"	1.5"	0.79"	T15	CS4X12	DC**11T3**


## CC\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D16-SCLCR/L06	16	0.79"	0.43"	-	0.79"	T8	CS2.5X6	CC**0602**
D20-SCLCR/L09	20	0.94"	0.51"	-	0.79"	T15	CS4X8	CC**09T3**
D25-SCLCR/L09	25	1.18"	0.67"	-	0.79"	T15	CS4X10	CC**09T3**
D32-SCLCR/L09	32	1.54"	0.87"	-	1.26"	T15	CS4X10	CC**09T3**
D40-SCLCR/L12	40	1.89"	1.06"	-	1.5"	T15	CS4X12	CC**1204**


# Turning damping tool head

## TC\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D16-STFCR/L11	16	0.79"	0.43"	-	0.79"	T8	CS2.5X6	TC**1102**
D20-STFCR/L11	20	0.94"	0.51"	-	0.79"	T8	CS2.5X6	TC**1102**
D25-STFCR/L16	25	1.18"	0.67"	-	0.79"	T8	CS2.5X8	TC**1102**
D32-STFCR/L16	32	1.54"	0.87"	-	1.26"	T15	CS4X10	TC**16T3**
D40-STFCR/L16	40	1.89"	1.06"	-	1.26"	T15	CS4X10	TC**16T3**


## VC\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D16-SVUCR/L08	16	0.83"	0.47"	-	0.79"	T6	CS2X6	VC**0802**
D20-SVUCR/L08	20	0.98"	0.55"	-	0.87"	T6	CS2X6	VC**0802**
D25-SVUCR/L11	25	1.26"	0.71"	-	0.98"	T8	CS2.5X8	VC**11T3**
D32-SVUCR/L16	32	1.54"	0.87"	-	1.26"	T15	CS4X10	VC**1604**
D40-SVUCR/L16	40	1.89"	1.06"	-	1.26"	T15	CS4X12	VC**1604**


# Turning damping tool head

**VC\*\***



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D20-SVQCR/L11	20	0.98"	0.51"	-	0.87"	T8	CS2.5X8	VC**11T3**
D25-SVQCR/L11	25	1.18"	0.63"	-	1.06"	T8	CS2.5X8	VC**11T3**
D32-SVQCR/L16	32	1.54"	0.83"	-	1.34"	T15	CS4X10	VC**1604**
D40-SVQCR/L16	40	1.89"	0.98"	-	1.34"	T15	CS4X10	VC**1604**


**VC\*\***



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D20-SVZCR/L11	20	0.98"	0.79"	1.06"	0.59"	T8	CS2.5X8	VC**11T3**
D25-SVZCR/L11	25	1.18"	0.87"	1.1"	0.59"	T8	CS2.5X8	VC**11T3**
D32-SVZCR/L16	32	1.54"	0.98"	1.38"	0.79"	T15	CS4X10	VC**1604**
D40-SVZCR/L16	40	1.89"	1.14"	1.38"	0.79"	T15	CS4X10	VC**1604**


# Turning damping tool head

## CN\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D32-DCLNR/L12	32	1.57"	0.87"	-	1.5"	T15	-	CN**1204**
D40-DCLNR/L12	40	1.97"	1.06"	-	1.5"	T15	-	CN**1204**
D40-DCLNR/L16	40	2.24"	1.26"	-	1.57"	T20	-	CN**1606**
D40-DCLNR/L19	40	2.24"	1.34"	-	1.65"	T20	-	CN**1906**


## DN\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D32-DDUNR/L11	32	1.57"	0.87"	-	1.26"	T15	-	DN**1104**
D40-DDUNR/L1504	40	1.97"	1.06"	-	1.26"	T15	-	DN**1504**
D40-DDUNR/L1506	40	1.97"	1.06"	-	1.26"	T15	-	DN**1506**


# Turning damping tool head

## TN\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D32-DTFNR/L16	32	1.57"	0.87"	-	1.42"	T15	-	TN**1604**
D40-DTFNR/L16	40	1.97"	1.06"	-	1.42"	T15	-	TN**1604**


## SN\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D40-DSKNR/L12	40	1.97"	1.06"	1.61"	1.5"	T15	-	SN**1204**
D40-DSKNR/L15	40	2.17"	1.14"	1.54"	1.42"	T20	-	SN**1506**


# Turning damping tool head

## VN\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D40-DVUNR/L16	40	2.05"	1.18"	-	1.42"	T15	-	VN**1604**


## WN\*\*



Type	D2	Dmin	F	L1	L	Wrench	Screw	Insert
D32-DWLNR/L12	32	1.57"	0.87"	-	1.42"	T15	-	WN**0804**
D40-DWLNR/L15	40	1.89"	0.87"	-	1.42"	T15	-	WN**0804**

★ All products accept customized non-standard sizes, delivery time: 30 days!


## Roughing



Type	DC	L2	L1	D1	D2	Model	Cartridge	Insert
RD2227C06-C32	0.87"-1.06"	5.51"	8.46"	0.83"	1.26"	C32	C90-2227C06	CC**0602**
RD2735C06-C32	1.06"-1.38"	6.69"	9.06"	1.02"	1.26"	C32	C90-2227C06	CC**0602**
RD3444C09-C42	1.34"-1.73"	8.27"	11.81"	1.26"	1.65"	C42	C90-3344C09	CC**09T3**
RD4154C09-C42	1.61"-2.13"	12.6"	16.53"	1.57"	1.65"	C42	C90-4154C09	CC**09T3**
RD4254C09-BT50	1.65"-2.13"	10.24"	14.17"	1.61"	1.97"	BT50	C90-4254C09	CC**09T3**
RD5170C09-BT50	2.01"-2.76"	12.8"	17.72"	1.97"	2.48"	Bt50	C90-5170C09	CC**09T3**
RD6282C12-BT50	2.44"-3.23"	15.75"	21.65"	2.4"	2.76"	BT50	C90-6282C12	CC**1204**
RD7295C12-BT50	2.83"-3.74"	17.91"	24.02"	2.8"	3.15"	BT50	C90-7295C12	CC**1204**
RD82120C12-BT50	3.23"-4.72"	-	20.47"	3.19"	-	BT50	C90-82120C12	CC**1204**
RD118120C12-BT50	4.64"-4.72"	-	25.59"	3.19"	-	BT50	C90-118120C12	CC**1204**

★ All products accept customized non-standard sizes, delivery time: 30 days!


## Finishing



Type	DC	L2	L1	D1	D2	Model	Cartridge	Insert
FD2228T08-C32	0.87"-1.1"	5.51"	8.46"	0.83"	1.26"	C32	C90-2228T08	TP**0802**
FD2735T08-C32	1.06"-1.38"	6.69"	9.06"	1.02"	1.26"	C32	C90-3735T08	TP**0802**
FD3444T11-C42	1.34"-1.73"	8.27"	11.81"	1.26"	1.65"	C42	C90-3444T11	TP**1102**
FD4255T11-C42	1.65"-2.17"	12.6"	16.53"	1.57"	1.65"	C42	C90-4255T11	TP**1102**
FD4255T11-BT50	1.65"-2.17"	10.24"	14.17"	1.57"	1.97"	BT50	C90-4255T11	TP**1102**
FD5370T11-BT50	2.13"-2.76"	12.8"	17.72"	1.97"	2.48"	Bt50	C90-5370T11	TP**1102**
FD6391T11-BT50	2.44"-3.58"	15.75"	21.65"	2.4"	2.76"	BT50	C90-6291T11	TP**1102**
FD73103T11-BT50	2.87"-4.06"	17.91"	24.02"	2.8"	3.15"	BT50	C90-73103T11	TP**1102**
FD83128T11-BT50	3.27"-5.04"	-	20.47"	3.19"	-	BT50	C90-83128T11	TP**1102**
FD83128T11L-BT50	3.27"-5.04"	-	25.59"	3.19"	-	BT50	C90-83128T11	TP**1102**

★ All products accept customized non-standard sizes, delivery time: 30 days!

# Milling damping tool



Type	D	M	D1	L1	L2	Model	H
BT50-D16-L170	16	M8*1.25	1.5"	6.69"	1.5"	BT50	0.67"
BT50-D16-L240	16	M8*1.25	1.5"	9.45"	1.5"	BT50	0.67"
BT50-D22-L260	22	M10*1.5	1.89"	10.24"	1.5"	BT50	0.71"
BT50-D22-L310	22	M10*1.5	1.89"	12.2"	1.5"	BT50	0.71"
BT50-D22-L320	22	M10*1.5	2.36"	12.6"	1.5"	BT50	0.71"
BT50-D22-L400	22	M10*1.5	2.36"	15.75"	1.5"	BT50	0.71"
BT50-D27-L400	27	M12*1.75	2.99"	15.75"	1.5"	BT50	0.79"
BT50-D27-L450	27	M12*1.75	2.99"	17.72"	1.5"	BT50	0.79"
BT50-D32-L400	32	M16*2.0	3.19"	15.75"	1.5"	BT50	0.87"
BT50-D32-L530	32	M16*2.0	3.19"	20.87"	1.5"	BT50	0.87"

★ All products accept customized non-standard sizes, delivery time: 30 days!